A CPG-driven Autonomous Robot

Jörg Conradt, Rodney J. Douglas, Institute of Neuroinformatics, ETH / University Zurich Paulina Varshavskava, CSAIL, Massachusetts Institute of Technology Kerstin Preuschoff, CNS, California Institute of Technology



uni | eth | zürich

Introduction

We have built an autonomous mobile robot which facilitates exploring motion principles based on neural Central Pattern Generator (CPG) circuits in a truly distributed system.

The main aim of the project is to demonstrate elegant motion on a robot with a large number of degrees of freedom under the control of a simple distributed neural system as found in many animals' spinal cord. Currently, the robot consists of up to 60 individual segments that all run a local CPG. Sparse adjustable short- and long-range counling between these CPGs synchronizes all segments, thus generating overall stable motion. A wireless connection between a host computer and the robot allows changing parameters during operation (eg. individual coupling coefficients, traveling speed, and motion amplitude). Additionally, users can modify the CPG algorithm and reprogram the segments during operation.

The robot can demonstrate various motion patterns based on extremely simple neural algorithms. We are currently implementing more advanced neural CPGs and will compare them in terms of motion robustness and traveling speed.

This poster presents the neural inspiration behind the robot (2, 3) as well as its physical design (4), discusses some experimental results in locomotion (5-7), and suggests some open questions for future research (8).

The Lamprey, a Simple Example for CPG-driven Locomotion

A Mathematical Model for CPG-driven Locomotion

A. E F. .. Current phase of the ith CPG oscillator


Frequency of the ith oscillator

$$\frac{d\theta_{i}}{dt} = \omega_{i} + \sum_{j=1}^{N} \alpha_{ij} \sin(\theta_{j} - \theta_{i} + \eta \ (i - j)) \quad \alpha \ll 1$$
Change of oscillator phase, depending on ω_{i} ,


coupling coefficients α_{ij} along the spinal cord,

$$\varphi_i = \varphi_{\text{max}} \sin(\theta_i)$$

Transform of instantaneous internal phase to external bending angle



phase offset *n* between neighboring segments



Physical Design of the Segments

· Small, lightweight design

Modular design

On-board power supply

True local control (CPG

· Local sensory input: rotary position, motor

· Reconfigurable inter-segmental connections (0 or 90 degrees)

Microcontroller | Almel MJ 2 4 LEDs to display internal states otentione ter for position tee door ki underneath PCB

Frontal view of a segment

· No paired fins sticking out

Pictures of lampreys

Oscillation frequency of body proportional to traveling speed


- Distributed CPG segments along the spinal cord
- Left and right alternating activity, traveling uniformly down
- · Intersegmental coupling to generate stable traveling wave One wavelength / body length (of roughly 100 segments)
- Other examples for CPG-driven motion; Eels, Snakes

Data and Image courtesy of Avis Cohen, University of Maryland

Activity of CPGs in a 50 segment isolated piece of spinal cord


- Strong enough to lift themselves
- 3-wire "spinal cord"
- (rechargeable battery)
- algorithm on segment)

torque, temperature, battery voltage, 3 x ambient light



- wireless communication with PC - report and modify states of all other segments

- reprogram CPG-algorithms during operation



5 Experiments

- · Robot motion in different mechanical configurations: - planar horizontal robot (snake-like)
- planar vertical robot (worm-like)
- alternating horizontal and vertical rotating segments (motion in 3D)
- Parameters for generating motion:
- frequency of oscillation in segments
- amplitude of oscillation in segments
- phase offset between neighboring segments
- coupling coefficients between segments
- Motion experiments in different environments:
- on table with fixated head and tail-segments
- on different surfaces, eg carpet, plastic, wood, stone
- Data collection:
- hand-recorded overall velocity (forward and sidewinding)
- sequences of desired and true angular positions

6 Results

- Simple CPG algorithm sufficient for generating various motion patterns: - sliding motion
- side-winding motion
- self-lifting traveling wave in planar and alternating configurations
- Parameter settings for efficient motion depend on the robot's configuration and on surface properties. Determining these parameters empirically is extremely time demanding
- Variations in the coupling coefficients have no effect on motion (above a critical threshold for synchronization)

Funded by the

Institute of Neuroinformatics, ETH / University of Zurich and by travel grants from the Neuromorphic Engineering's Research Collaborative Network (INE-RCN)

Discussion

Large number of segments, high number of degrees-of-freedom, inherently scalable

Robust and failure tolerant system

Elegant control by an incredibly simple model

Highly complex motion patterns relative to algorithmic cost

Different mechanical configurations possible

We do not suggest that the robot is a good approximation to a biological system. Rather, we hope that the distributed nature of the robot's control will allow for interesting experiments pertaining to the function of the spinal cord or other, possibly artificial, neural system.

Further documentation and demonstration videos of the robot are available on the web at:

http://www.ini.ethz.ch/~conradt/projects/WormBot

Future Directions

- · Integrating local sensor signals (adapting local CPG behavior to external stimuli)
- · Implementing more detailed CPG algorithms
- · Adding an accelerometer, using signals to learn parameters for efficient forward motion
- · Stabilizing the head during motion (accelerometer)
- · Adding vision, processing data onboard (eg. simple color blob tracking), goal directed motion
- · Finding sparse coupling network
- · Commercializing the robot: targeting academia or the tov-market?

References:

Cohen, A.H., Holmes, P.J., Rand, R.H. (1982). The Nature of the Couplings Between Segmental Oscillators of the Lamprey Spinal Generator for Locomotion: A Mathematical Model, in Journal of Mathematical Biology, Vol.13, pp.345-369.

Dowling, K.J. (1997), Limbless Locomotion: Learning to Crawl with a Snake Robot, PhD Thesis, CMU

 Conradt, J., Varshavskaya, P. (2003). Distributed Central Pattern Generator Control for a Serpentine Robot, Joint International Conference on Artificial Neural Networks and Neural Information Processing (ICANN/ICONIP), Istanbul, Turkey.